

# Miller 219WRS Manyard® Shock-Absorbing Lanyard

## Description

The 219WRS Manyard Shock-Absorbing Lanyard is a “connecting device” for fall protection applications. It features a special woven shock-absorbing inner core that reduces fall arrest forces. The heavy-duty tubular outer jacket serves as a back-up web lanyard. It features one locking snap hook and one locking rebar hook. Sizes are available from 4-ft. to 10-ft.

## Materials

### Webbing:

- Safety Strap/Jacket: Yellow tubular polyester webbing
- Shock-absorbing web core: polyester, 1” elastic

**Min. Tensile:** 5,000 lbs. (22kN) on webbing

**Thread:** 6 cord bonded 3 strand polyester thread, with a minimum tensile of 42 lbs.

**Hardware:** Steel Minimum Tensile strength

- Locking Snap Hooks: 5,000 lbs. (22kN)  
3/4 in. (19mm) gate opening
- Locking Rebar Hooks: 2 ½ in. (63mm) gate opening

*\* All hardware meets ASTM (50) fifty-hour salt spray test requirements.*

**Label Materials:** Valeron

## Technical

### Max Working Load Capacity

Max. Working Load: 310 lbs (141 kg)

## Certification

OSHA 1926.502, 1910.66; ANSI A10.32 and CSA Z259.2.2 Type 1



**MILLER®**  
by SPERIAN

Toll Free 800.873.5242 • Phone 814.432.2118 • Fax 800.892.4078 • [www.millerfallprotection.com](http://www.millerfallprotection.com)

**WARNING!** THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.