

Cooling Air Harness

The SED Cooling Air Harness provides critical cooling air for personnel in hot environments as well as breathing and/or purging air while wearing disposable suits.



COOLING AIR HARNESS:

Size Height, shoulder to ankle. One size fits all.

Attachment Straps At wrists and ankles, weight rests on shoulders

Material Elasticized strap, fastening Male and Female

dome snaps

3 adjustment sizes (unstretched)

To Harness Dome fastener to permit cleaning & replacement

HARNESS AIR CHANNELS:

Materials PVC coated nylon scrim, both sides

Weight 250-500 g/m2

Air Dispersion Method -- 1 row of holes inner

surface only to provide cooling

Working Pressure 70 psig

Air Flow (Design Requirement) Through Full Air Harness, 28 +/- 2 scfm @ 75 +.-

5 psig

CONNECTION HOSE:

Size 1 cm (3/8") ID, 2 cm (1.5") OD

Length 56 cm

Jacket Imprint Goodyear "Ortac"

Hose Material working pressure 200 psig, nominal

Hose Colour Red

rtcu

CONNECTOR, AIR ONLY: Type -- Hanson (Model #2L22), Male

NOISE LEVEL:

Measurement Method

Supplied with air at 75 psig @

Harness suspended vertically with arm extensions hanging free

Meter to be placed 50 cm on the horizontal plane of the chest piece

CONNECTOR, COMBINED AIR/COMMUNICATIONS, if so equipped:

SED Specification S-1010 Male Air Plug Insert,

S-1012 Socket Air/Communication Connector

S-1013 Molded Component

Colour Blac

Air Fitting Type Hansen 2RL compatible per SED #CN0005A3,

Male #200109-2

Material Stainless Steel

Electrical Fitting Type Male: Cannon XLR-3-12C insert or equivalent

Female: Cannon XLR-3-11C

Conductors 3
Boot Colour Red

www.sed.bz

Model numbers

CAH-03 Breathing Air Only Cooling Harness
CAH-01 Combined Breathing & Communication Cooling Harness

1-800-665-2740 1-519-396-8555