

Model: FP9S6ACC5, FP9S6AAA5

Description:

This double leg lanyard is designed with 12ft (3.7m) Free Fall Energy Absorber which allows the worker weighing between 100-310lbs (45 - 140kg) to connect at feet level. Fall Clearance must be calculated. This lanyard has options of double locking aluminum large snaps or small snaps. The legs are stretch which contracts from 5ft to 3.5ft (1.5 to 1.1m) when relaxed.



SIZE	5ft (1.5m) - contracts to 3.5ft (1.1m)	COUNTRY ORIGIN	Canada
TYPE	12ft (3.7m) Free Fall Energy Absorber Lanyard	HARDWARE STANDARD	CSA Z259.12-16
CLASSIFICATION	Class Y	WEIGHT RANGE	100-310 lbs (45-140 kg)
STANDARD	Meets and Exceeds CSA Z259.11-17, ANSI Z359.1-07.	AVERAGE ARRESTING FORCES	4 kN (900lbs)
MATERIAL DATA	Polyester Webbing, Aluminum Hardware	DEPLOYMENT DISTANCE	60" (1.5m) for 12ft (3.7m) free fall 30" (0.8m) for 6ft (1.8m) free fall
COLOR	Black Webbing. Hardware is Silver or Black.	HARDWARE TENSILE	6000 lbs (27 kN)

Training and appropriate use:

Please refer to the product manual included with the products before using.
Failure to follow the manufacturer's instructions can lead to injury, illness or even death.

For additional information: 1-877-446-3278

Revision 2: August 18, 2020