



990GY Tigerhood Classic

Description

Thermoplastic welding helmet. Seamless design sheds sparks and spatter. Unique shape combines straight and curved front for better protection from smoke and fumes. Can be used for most over head welding applications. 4 ½" x 5 ¼" Fixed front glass holder. 24 square inches of unobstructed viewing. Comes complete with shade 10 polycarbonate lens and free floating 3-C headgear. SEI Certified

Window Size	4.5" x 5.25"
Material	Noryl
Visible Light Transfer (VLT)	N/A
Headgear Style	Ratchet (size 6 ¾" to 8")
Replacement Headgear	3C
Replacement Filter	P457SH10 (other shades available; inquire)
Replacement Sweatband	FM44TV
Magnifier option (Yes/No)	Yes
Hardhat Options (Yes/No)	Yes
Other Available Colors	Black, Silver, Blue
Dielectric Frame	N/A
Standards Passed	ANSI Z87.1; CSA Z94.3



Technical Specifications

Packaging	1/Box; 8 ea/Case (also available in bulk 10/box)
Unit Weight	2 lbs.
Case Weight	17 lbs.
Case Dimensions	20.5" x 29.0" x 19.0"
MSDS Requirements	None required
Harmonization Code	6506.10.6075

WARNING: This reference manual provides only an overview of the products shown. It does not provide important product warnings and instructions. Honeywell Safety Products recommends that all users of its products undergo thorough training and that all warnings and instructions provided with the products be thoroughly read and understood prior to product use. It is necessary to assess hazards in the work environment and to match the appropriate personal protective equipment to particular hazards that may exist. A complete and thorough hazard assessment must be conducted to properly identify the appropriate personal protective equipment to be used in a particular work environment. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS AND TO PROPERLY PERFORM A HAZARD ASSESSMENT MAY RESULT IN SERIOUS PERSONAL INJURY, ILLNESS OR DEATH.

