

Model: FP6311/4, 6



Description:

Web Lanyard. The webbing is made of synthetic material.

This product shall be integrally connected to other fall arrest system components or elements.

This product is certified by CSA; Meet and exceed the ANSI & OSHA as well.

Single user only.

Multi-sizes are available.

Ideally to use *Dynamic Energy Absorber* with this product for fall protection.

SIZE	4', 6', 8', 10', 12' long	WEIGHT	1.24 lbs (0.56 kg)
TYPE	Web Lanyard	MATERIALS	High Strength Steel Snaps; 1" Width Polyester Webbing
CSA CLASS	Class B	MAX WORK LOAD	400 lbs (180 kg)
STANDARDS	CSA Z259.11-17, ANSI Z359.1-07	HARDWARE MIN TENSILE	6000 lbs (27 kN)
HARDWARE	Certified to CSA Z259.12-16; ANSI/ASS Z359.12-19	MAX. ARREST FORCE	1300 lbs (6 kN) or less
COLOR	Golden or Silver Snaps; Red Lanyard	MADE IN	Canada

**Training and Proper Use: Please refer to product manual included with the products prior to use.
For Additional Information: 1-877-446-3278**

Revision 2, April 9, 2020
L'information en français est disponible

Head Office

2477, Michelin, Laval, Qc H7L 5B9
T: (450) 622-7374/ 1 877 446-3278
F: (450) 622-2243/ 1 877 463-2789

Fall Protection Manufacturing

175 Admiral Blvd., Mississauga, On L5T 2T3
T: (905) 565-9990
F: (905) 565-9906

