Honeywell <u>M</u>iller

Miller Scorpion[™] Personal Fall Limiter

Description

The lightweight, compact design of the 9 ft. (2.7 m) Miller Scorpion Personal Fall Limiter provides workers an affordable alternative to shock-absorbing lanyards. In a head-to-head comparison with shock-absorbing lanyards, the Scorpion web retractable requires less fall clearance, offers greater mobility and prevents tripping hazards.

Materials

| Thermoplastic Cover/Aluminum Extrusion |
|--|
| Polyester |
| Zinc #3 |
| Stainless Steel |
| Polyester/Vectran |
| |

Technical

Max. Working Load: Working Length Capacity: Max. Arrest Distance: Avg. Arresting Force:

Max. Arresting Force:

310 lbs. (140.6 kg) 9 ft. (2.7 m) 24 in. (0.6 m) ≤ 900 lbs. (4 kN) (When tested to ANSI Z359.14) 1,800 lbs. (8 kN) (When tested to ANSI Z359.14)

Certifications

Meets OSHA 1926.502, OSHA 1910.140, and ANSI Z359.14-2014 Class A and B requirements.



TECHNICAL DATA SP106 Rev G 5-19

Miller Scorpion[™] Personal Fall Limiter

| Model | Unit Connector | Lanyard End Connector | Weight |
|---------------|--|--------------------------------|--------------------------------|
| PFL-1-Z7/9FT | No unit connector | Steel Locking Snap Hook | 2.9 lbs. (1.3 kg) |
| PFL-2-Z7/9FT | Steel Twist-Lock Carabiner | Steel Locking Snap Hook | 3.5 lbs. (1.6 kg) |
| PFL-3-Z7/9FT | Stainless Steel Swivel Shackle | Steel Locking Snap Hook | 3.1 lbs. (1.4 kg) |
| PFL-4-Z7/9FT | Steel Twist-Lock Carabiner and Swivel Shackle | Steel Locking Snap Hook | <mark>3.7 lbs. (1.7 kg)</mark> |
| PFL-5-Z7/9FT | D-Ring Swivel Hook | Steel Locking Snap Hook | 3.3 lbs. (1.5 kg) |
| PFL-6-Z7/9FT | Steel Locking Rebar Hook and Swivel Shackle | Steel Locking Snap Hook | 4.4 lbs. (2.0 kg) |
| PFL-7-Z7/9FT | Steel Locking Snap Hook and Swivel Shackle | Steel Locking Snap Hook | 3.7 lbs. (1.7 kg) |
| PFL-8/9FT | Captive Eye Carabiner | Steel Locking Snap Hook | 3.5 lbs. (1.6 kg) |
| PFL-15-Z7/9FT | No unit connector | Steel Locking Swivel Snap Hook | 3.1 lbs. (1.4 kg) |
| PFL-16-Z7/9FT | Steel Twist-Lock Carabiner | Steel Locking Swivel Snap Hook | 3.7 lbs. (1.7 kg) |
| PFL-17/9FT | No unit connector | Web Loop For Carabiner | 2.3 lbs. (1.0 kg) |
| PFL-18-Z7/9FT | Aluminum Twist-Lock Carabiner and Swivel Shackle | Aluminum Locking Snap Hook | 3.5 lbs.(1.6 kg) |
| PFL-19-Z7/9FT | Aluminum Locking Rebar Hook and Swivel Shackle | Aluminum Locking Snap Hook | 4.0 lbs. (1.8 kg) |
| PFL-20-Z7/9FT | Aluminum Locking Snap Hook and Swivel Shackle | Aluminum Locking Snap Hook | 3.7 lbs. (1.7 kg) |
| PFL-21-Z7/9FT | Aluminum Locking Snap Hook and Swivel Shackle | Aluminum Locking Rebar Hook | 4.1 lbs. (1.9 kg) |

Limitless Possibilities. Ask the Expert. Technical Service: 800.873.5242 www.millerfallprotection.com

Honeywell Industrial Safety 900 Douglas Pike Smithfield, RI 02917

USA Phone: 800.430.5490 Fax: 800.322.1330 Canada Phone: 888.212.7233 Fax: 888.667.8477 This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.